



**UK-WER-0041-01**

**1. Unique identification code of product-type:**

PARA/RW6

**2.Type, Batch or serial number as required pursuant to Article 11(4):**

See UK-WER-0041-01 english : See batch number displayed in product

**3. Intended use or uses of construction product, in accordance with the applicable harmonized technical specification:**

Thermal Insulation for Buildings, See UK-WER-0041-01 english

**4. Name, registered trade name or registered trade mark and contact address as required pursuant to article 11(5):**

FSi Limited, Westminster Industrial Estate, Tamworth Road, Measham, DE12 7DS, UK.  
Rockwool Limited, Pencoed, Bridgend, CF35 6NY

**5. Authorized representative: N/A**

**6. System or systems of assessment and verification of performance of the construction product as set out in Annex V: AVCP - System 1 and System 3**

**7. Harmonized standard: BS EN 13162:2012 Issued on 28 February 2013**

**8. In case of the declaration of performance concerning a construction product for which a Declaration of Performance has been issued:**

The performance of the product identified is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

**9. Declared performance: Please refer to the table below (NPD - No Performance Determined)**

Essential Characteristics	requirement clauses in this European Standard	Level and / or classes	Declared value
Reaction to fire Euroclass characteristics	4.2.6 Reaction to fire	Euroclasses	A1
Resistance to Fire	Etag 026	-	NPD
Release of dangerous substances to the indoor environment	4.3.13 Release of dangerous substances	-	NPD
Acoustic absorption index	4.3.11 Sound absorption	Declared $\alpha_p$ and $\alpha_w$	NPD
Thermal resistance	4.2.1 Thermal resistance and thermal conductivity 4.2.2 Length and width 4.2.3 Thickness 4.2.4 Squareness 4.2.5 Flatness	Declared $R_{90/90}$ and / or $\lambda_{90/90}$ Declared l and b Declared d or tolerance class T Declared $S_b$ Declared $S_{max}$	$\lambda(90/90) = 0.035$ W/mK $\pm 3$ mm width of line and $\pm 5$ mm length of line T4 $\pm 2.5$ per 500mm $\pm 6$ mm
Durability of reaction to fire against heat, weathering, ageing/degradation	4.2.7 Durability characteristics <sup>a)</sup>	b)	NPD
Durability of compressive strength against ageing / degradation	4.3.6 Compressive creep	Declared $X_{ct}$ and $X_t$	NPD

**10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**

Signed for and on behalf of the manufacturer by:



20/05/2016

**C. Atkinson - Managing Director**



20/05/2016

**L. Peach - Technical Manager**